

## StarGlow II for 3-Cylinder



Hözl glow plug regulator for 3-cylinder radial engine

Rating: Not Rated Yet

Base price with tax

Selling price:163,87 €

Selling price without VAT:163,87 €

VAT:

[Ask a question about this product](#)

Link to our Gallery - [StarGlow II for 3-Cylinder with Saito FA 120 R3](#) in model air plane Robbe Pander

### Description:

- redesigned board: with SMD parts and microcontroller (high resistant for vibration)
- double boards with double-sided mounting (compact construction)
- **integrated pulse amplifier (Receiver amplifier)**
- **low electricity intake because of clocked system**
- **glow current functioning** by control modules (for **each glow plug a separate poti**)
- **integrated voltage control** of accu
- **no damage by overvoltage** - when one glow plug fails, the other glow plugs are not influenced

- LED-display at regulator, **direct LED-Display of the glow plug's functioning**
- LED-diplay with bright diodes (blue)
- **integrate test output plug** - for continuous Operation without remote control (e.g. test-station)
- including on/off installed
- **including multiplex battery adapter cable** installed (produced at **PowerBox Systems**)
- including positive cable with screws and discs, gold plug
- Receiver connecting cable: Graupner/JR servo cable with gold contacts ([VOGEL-BLUE-LINE-SILICON](#))

### **Glow Battery:**

The glow battery should have a voltage of

- 7,4 V (2x LiPo-cells) or
- 7,2 V (6x NiXX-cells)

The capacity should be chosen according to the number of glow plugs.

For 30 minutes of constant glowing the following applies approximately:

- 3 glow plugs -> 1200 mAh
- 5 glow plugs -> 1800 mAh
- 7 glow plugs -> 2400 mAh
- 9 glow plugs -> 3000 mAh

### **Programming:**

- easy programming (external LED to display the programming functioning)
- main functions are programmable by remote control

### **Technical Datas:**

- Dimension: 68 x 46 x 25 mm
- Weight 90 g

### **Scope of delivery:**

- Glow plug regulator
- Multiplex battery Adapter cable
- On/off switch

- Positive cable to engine incl. screws and discs
- four fastening screws
- Screwdriver PH00 (to adjust the Poti)

### Accessory:

- see [Accessory](#) for StarGlow II

 [User Manual](#)

Delivery: on stock

Units in box: 1